

# NASA TECH BRIEF



NASA Tech Briefs are issued to summarize specific innovations derived from the U.S. space program, to encourage their commercial application. Copies are available to the public at 15 cents each from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia 22151.

## Improvement in Recording and Reading Holograms




FIGURE 1

A three-beam technique has been developed to superimpose a number of patterns in the same plane of a hologram and then to uniquely identify each pattern by a suitable readout process. In contrast to prior techniques, the developed readout process does not require any movement of parts.

Figure 1 illustrates both the prior art and the technique developed. Coherent collimated light L is incident upon a Rayleigh lens R and upon a pattern I to be holographically recorded. The Rayleigh lens R focuses the incident light L to a point F which should appear in the same plane as the input pattern I (plane normal to the 0-0' axis). The light diverges from F to the transform lens T, which is located one focal distance from the plane of pattern I. The light amplitude in the back focal plane of the transform lens T is equal to the Fourier transform of the input pattern I. The interference between the Fourier transform and the beam of light emanating from F is recorded on a photographic plate P placed at the back focal plane of lens T.

The above description is common to both the prior art and the new three-beam method; however, the method for storing additional patterns is different. In the prior art, one would rotate the photographic




FIGURE 2

plate P about an axis perpendicular to axis 0-0' by some finite angle and then repeat the steps outlined above. The three-beam technique introduces another lens B which comes to a focus at a point G in front of the photographic plate P.

When a new pattern is to be stored, the location of lens B is changed in such a manner to keep constant the distance from the center of lens B to the axis 0-0' as well as the distances from the center of the plate P to point G and from point G to the center of lens B (i.e., a rotation about the 0-0' axis). Now there are three beams interfering at the photographic plate P.

The distinct advantage of the three-beam technique can be seen in Figure 2, which displays the readout process of the images stored on the photographic plate P. An unknown pattern is placed in a window formed by the stops S; the collimated coherent light L will pass only through the pattern I. The transform lens T performs the Fourier transform of the pattern, and in the plane of the photographic plate P the Fourier transform is multiplied with the previously recorded Fourier transforms. Lens A then performs another Fourier transform and exhibits the cross correlation of the input pattern I with all the stored patterns as a

(continued overleaf)

point of light  $F'$ . Using just the prior art, one would have to rotate the photographic plate  $P$  in order to search for the formation of point  $F'$ , and the angle of the plate  $P$  will indicate which of the stored patterns is matched by the input pattern  $I$ . In the three-beam technique, point  $F'$  will be present without any movement of plate  $P$ ; there will also be another point of light  $G'$  which is the image of point  $G$  of Figure 1. The position of point  $G'$  indicates which of the stored patterns matches the input pattern  $I$  (if any). (As noted in Figure 2, there is also an image  $I'$  of the input pattern  $I$ .)  $F'$  and  $G'$  come to a point focus in different planes which is convenient for readout purposes. Thus, the new three-beam technique allows one to interrogate the stored patterns for a matching pat-

tern in one operation, without the previously required need for moving the photographic plate  $P$ .

**Note:**

Details may be obtained from:

Technology Utilization Officer  
Electronics Research Center  
575 Technology Square  
Cambridge, Massachusetts 02139  
Reference: B68-10347

**Patent status:**

Inquiries about obtaining rights for the commercial use of this invention may be made to NASA, Code GP, Washington, D. C. 20546

Source: J. N. Hallock  
(ERC-10151)